

# Oil Quality Meter

## Tribocheck



### Technical Data

Type	Tribocheck
Oil quality measuring range	0% ... 100%
Oil measurement temperature range	0°C ... +80°C (32°F ... 176°F)
Resolution	1%
Measuring range temperature	0°C ... +220°C (32°F ... 428°F)
Resolution	1°C (1.8°F)
Accuracy	±1°C (±1.8°F)
Probe length	130 mm
Sensor element	V4A, gold and ceramic
Measurement result	after 5 seconds
Dimensions	125 x 54 x 22 mm
Battery	lithium, 3.6V

### Tribocheck



### Applications

- |  |   |  |
|--|---|--|
| <ul style="list-style-type: none"> <li>• For all transmission, hydraulic and motor oils</li> </ul> | <ul style="list-style-type: none"> <li>• Trucks</li> <li>• Construction machines</li> </ul> | <ul style="list-style-type: none"> <li>• Industrial hydraulic systems</li> </ul> |
|--|---|--|

### Attributes

- |   |  |  |
|---|--|--|
| <ul style="list-style-type: none"> <li>• Reliable determination of lubricating ability and pressure resistance</li> </ul> | <ul style="list-style-type: none"> <li>• Measurement directly in the fine filtering system (present or to be installed)</li> </ul> | <ul style="list-style-type: none"> <li>• Result visible on the display in 5 seconds</li> <li>• Easy operation</li> </ul> |
|---|--|--|

Description	Type	Part No.
Oil Quality Meter (incl. protective cover AG 140 and transport case)	Tribocheck	1340-1515
Tribocheck with Viscoprack, injection syringe and accessories with case*	Tribocheck-Set with Viscoprack	1340-1517

\*See picture page 38