

Vibration Meter Sound Level Meters

	
VIBRATION METER SOUND LEVEL METER	SOUND LEVEL METER
PIEZO ELECTRIC SENSOR 3 ½ DIGIT LCD DISPLAY D - 83 : DISPLACEMENT 0 - 2000 microns pk - pk D - 93 : DISPLACEMENT 0 - 2000 microns pk - pk & VELOCITY 0 - 200 mm / sec pK	CONDENSER MICROPHONE ANALOGUE METER RANGE : 40 dB - 140 dB RESPONSE : FAST & SLOW A & C WEIGHT AGE
WEIGHT	WEIGHT
SENSOR - 200 gms.	SENSOR - 130 gms
INSTRUMENT - 460 gms.	INSTRUMENT - 655 gms.
TOTAL WITH CARRY CASE - 1100 gms.	TOTAL WITH CARRY CASE - 1080 gms.

VIBRATION AND SOUND ARE TWO MOST IMPORTANT PARAMETERS FOR MONITORING THE MACHINE HEALTH. REGULAR LOGGING OF THESE TWO PARAMETERS PROVIDES EARLY WARNING OF BREAKDOWN
 WE ARE OFFERING PORTABLE INSTRUMENTS FOR INDIVIDUAL PARAMETERS AS WELL AS AN INTEGRATED METER.



VIBRATION & SOUND LEVEL METER - MODEL : VS-2000

VIBRATION	SOUND
3 ½ DIGIT DISPLAY	ANALOGUE METER
DISPLACEMENT : 0 - 2000 microns pk-pk	40 dB TO 140 dB RANGE
VELOCITY : 0 - 200 mm / sec pk	A & C WEIGHTAGE

Office Address : E/6, Udyog Sadan No.2, MIDC, Andheri (E), Mumbai - 400 093.
Maharashtra, INDIA Tel. : +91-22-66921091, +91-22-66921092, +91-22-28323676, Fax
: +91-22-28221736, Web : www.acdmachines.com, Email : info@acdmachines.com