

LCR-010P

Portable LCR Meter



FEATURES

- Portable meter
- Measures basic parameters L, C and R
- Large LCD display
- Backlit LCD
- Maximum count 1999
- Over range display
- Low Battery Warning
- Data Hold
- Function symbol display
- Polarity : automatic, positive implied, negative polarity indication

SPECIFICATIONS

BASIC FUNCTION	RANGE	ACCURACY
Inductance	200 μ /2m/20m/200m/2/20H	$\pm (2\% + 5)$
Capacitance	200P/2n/20n/200n/2 μ /20 μ /200 μ /2000 μ F	$\pm (2\% + 5)$
Test Frequency	400 Hz on 200 μ F to 20 μ F range 80 Hz on 20 μ F to 200 μ F range 100 Hz on 2000 μ F range	
Resistance	20/200/2K/20K/200K/2M/20M Ω	$\pm (0.8\% + 2)$
LCD MAX. Count	1999	
LCD Screen Size	49 x 60mm	

GENERAL SPECIFICATIONS

Operating Temperature and Humidity	0~40°C, <=70% RH
Power Source	9V - 242V, 47.5Hz - 63Hz
Battery Life	30 hours

ACCESSORIES	Test Leads, Battery, Instruction Manual
-------------	---

FALCON ELECTRO - TEK PVT. LTD.

Hema Industrial Estate, Near Meghwadi Police Station, Sarvoday Nagar, Jogeshwari (East), Mumbai - 400 060. INDIA.
Tel: +91-22-28348429 / 28248665 / 28346339 / 28343608 Fax: +91-22-28370165.
Email: falcon@falconindia.biz Website: www.falconindia.biz