

HYDMOC Slideways ISO VG 32 / 46 / 68

General purpose machinery oils specially formulated with additives to improve adhesiveness and film strength characteristics.

Total Acid Number (TAN)

TAN of any other slideway lubricating Machine oil 68 new should be always less than 1.

For every type of lubrication or hydraulic systems TAN should be lesser than 1.

Our DNR Corporation launches first time in india this concept should be taken care before purchasing from out source. Our Slide way Hydmoc Machine oil 68 has **TAN of 0.00022** means if it gets mixed with metal working fluid than also it will not contaminate MWF.

Hence life of MWF (Metal Working Fluid) will increase drastically.

Application Areas:

Lubricating are general-purpose lubricants -for 'once-through' application situation in textile mills, paper mills and machine tools.

Slideway oils grades are specially developed for general-purpose lubrication, to be used at steel mills, textile mills, machine tools, cnc vmc machines etc.

Performance Benefits:

Hydmoc series have proved, persistence of oil film to an unusual degree and have marked influence in reducing power consumption, wear and maintenance costs.

Our Slide way Hydmoc Machine oil 68 has **TAN of 0.00022** means if it gets mixed with metal working fluid than also it will not contaminate MWF.

Hence life of MWF will increase drastically.

Pack size ; 35 / 50 / 210 ltrs^l Plastic Hdpe Barrel.

Quality Is An Art For Others

.... But it Habit For Us

www.dnrcorporation.com