

H 3530

Fast horizontal door



Opens quickly, crashes virtually excluded

Our quickest door for internal applications. The door leaves quickly open to the sides and immediately make the full passage height available. This guarantees fast traffic flow and increases safety, above all for personnel traffic. Despite the fast opening speed of 3 m/sec., soft start and stop are guaranteed by the frequency converter control, which reduces the door's wear.

Further benefits: two opening widths can be programmed for personnel and vehicles. Closing edge safety devices and photocells provide additional safety. In the event of a malfunction, the door can quickly be opened with a hand pulley or automatically during a power failure by using an operating current brake (special equipment).

The entire operator technology is arranged on the right

in a space-saving manner in 3-sided cladding and only requires minimum headroom.



In the stainless steel version, the door fulfils the hygienic requirements of the food, chemical and pharmaceutical industries.

Internal door	H 3530
Size range	
Max. width (LDB)	3500 mm
Max. height (LDH)	3500 mm
Speed	
With standard FU control BK 150 FUE H	
Max. opening speed	3.0 m/sec.
Max. closing speed	1.0 m/sec.
Emergency opening	
Springs with pull cord	
Optional:	
Springs with operating current brake	
Curtain	
Fabric thickness	1.5 mm
Vision panel thickness	2.0 mm
Wind lock strip colours	
RAL 1018 Zinc yellow	
RAL 2004 Pure orange	
RAL 3002 Carmine red	
RAL 5010 Gentian blue	
RAL 7038 Agate grey	