

ENTERPRISES PVT. LTD. HOUSE OF IMPORTED HOT AIR GUNS.

B/28 B, Gr.Flr., Ghatkopar Indl.Est., Agra Road Indl.Pre., L.B.S.Marg, Ghatkopar(W), Mumbai-86. Office Tel.:(22) 32662113/67989551/67989552 Fax:(22) 67989553 email:heatgun@vsnl.com
Web: www.hotairguns.com www.hotairguns.in www.hotairguns.in www.hotairguns.in

Ultratorch® Model UT-35

A professional


quality, economical Ultratorch




- Standard with UT-35 iron with protective cap and a unique 1.6mm chisel type preheat tip mounted.
- Completely portable, lightweight and easy to handle, does not require cords, batteries or cartridges.
- Adjustable temperature control quickly regulates power to the tip, equivalent to a 20-60 watt electric soldering iron.
- Features unique iron plated, multifunction, corrosion resistant, preheat solder tips which work as both a soldering and flameless heat tip at the same time.
- Unique tips heat up quickly and last longer.
- Built-in window indicates fuel level.
- Refill with Master Ultratane® Butane for best performance.
- GS/TUV Listed for user safety
- Use to pinpoint heat, remove surface mount components, repair vinyl, shrink heat shrinkable tubing, solder & desolder, spot dry, strip insulation with hot knife and more

ORDERING INFORMATION

MODEL NO.	DESCRIPTION
UT-35	Professional quality, entry level, butane gas powered soldering iron/torch/heat tool
	& 1.6mm chisel preheat tip







ENTERPRISES PVT. LTD. HOUSE OF IMPORTED HOT AIR GUNS.

B/28 B, Gr.Flr., Ghatkopar Indl.Est., Agra Road Indl.Pre., L.B.S.Marg, Ghatkopar(W), Mumbai-86. Office Tel.:(22) 32662113/67989551/67989552 Fax:(22) 67989553 email:heatgun@vsnl.com

Web: www.hotairguns.com www.hotairguns.in www.heattool.com

OPTIONAL ACCESSORIES

PART NO.	DESCRIPTION	PART NO.	DESCRIPTION	
60-01-52	Heat Tip	60P-1.2D	1.2mm Chisel Preheat Soldering Tip	
60-02	Protective Cap	60P-1.6D	1.6mm Chisel Preheat Soldering Tip	
60-07U	Ejector Unit	60P-0.5B	.5mm Needle Preheat Soldering Tip	
60P-1	.2mm Needle Preheat Soldering Tip	60P-K	Hot Knife Preheat Tip	
60P-1C	1mm Tapered Needle Preheat Soldering Tip			

SPECIFICATIONS

■ Dimensions: 7.3" L (185 mm) w/o cap

■ Recommended Fuel: Master Ultratane® Butane ■ Equivalent to Electric Iron: 20 to 60 Watt

■ Approx. Operating Time: 60 min.

■ Approx. Solder Tip Temp.: 932° F (500° C)

■ Approx. Knife Tip Temp.: 932° F (500° C)

■ Approx. Heat Tip Temp.: 1200° F (650° C)

■ Approx. Torch Tip Temp.: 2370° F (1300° C)

■ Gas Tank Capacity: 12 ML

■ Net Weight: 2.6 oz. (74 g)

■ Shipping Weight: 1 lb.

Shipped Empty