AVTECH AVC561V, 565V REGULAR CAMERA



OVERVIEW

Equipped with a 1/3" SONY Super HAD Color CCD image sensor, this camera series has the satisfactory minimum illumination to provide clear and sharp images, and has a microphone built-in to consolidate the safety of your surveillance environment.

FEATURES

- (1) 1/3" SONY Super HAD Color CCD image sensor
- (2) Low light sensitivity of 0.5 Lux at F2.0
- (3) Built-in microphone

SPECIFICATIONS

| MODEL | AVC561V | AVO | C565V |
|---------------------|---|-----------|-------------|
| Pick up Element | 1/3" SONY Super HAD Color CCD image sensor | | |
| Number of Pixel | 510(H)x492(V) <ntsc> / 500(H)x582(V) <pal></pal></ntsc> | | |
| Resolution | 350 TV lines | | |
| Min. Illumination | 0.5Lux/F2.0 | | |
| S/N Ratio | More than 48dB (AGC off) | | |
| Electronic Shutter | 1/60 (1/50) to/100,000 sec. | | |
| Lens Mount | CSorC Mount | | |
| IRIS Mode | AES/VD/DD | | |
| BLC | ON / OFF | | |
| Gain Control | NORMAL / MAX | | |
| Flickerless | ON / OFF | | |
| White Balance | ATW | | |
| Video Output | 1.0 Vp-p composite, 75Q | | |
| Microphone | Built-in | | |
| Power Source (±10%) | DC 12V | AC230V | AC24V/DC12V |
| Current Consumption | 95mA | ~ | |
| Power Consumption | - | 2.0W max. | 2.8W max. |
| Dimension (mm)** | 118(L)x62(W)x50(H) | | |
| Gross Weight (g) | 235 | - | - |

The specifications are subject to change without notice. ** Dimensional Tolerance: ± 5mm

Address - 22, Oasis Industrial Estate, opp.Vakola. Masjid Santacruz (East) Mumbai - 400055

E-mail - ravinder@gurutek.co.in . website - www.gurutek.co.in

Tel - 022 32521053 / 9699031115