

PRODUCT SPECIFICATION

KPC133E

1/3" H.R Color CCD IR Camera

Overview

1/3" H.R. color CCD, Satisfied minimum illumination: 0.1 Lux/ F2.0, 0Lux (IR ON), IR distance: over 15 meters with 21 IR LEDs.

Features

- High sensitivity in the dark environment, 0.1Lux/ F2.0, 0Lux (IR ON)
- Day and night features for 24-hour surveillance
- Excellent image quality (500 TVL High Resolution)
- 21 nos. IR LED effective range reaches up to 15 meters

Specification

MODEL

Pick up Element
Number of Pixels
Resolution Min.
Illumination Effective
Range IRLED S/N
Ratio Electronic
Shutter Lens
Lens Angle IRIS Mode
White Balance Video
Output Power Source
Current Consumption
Dimensions (mm)**
Country of Origin

KPC133E

1/3" H.R. color CCD
image sensor
771(H) x
492(V)<NTSC>/
753(H) x
582(V)<PAL>
500TV lines
0.1Lux/F2.0, 0Lux
(IRLED ON)
Over 15 Meters
21 units
More than
48dB(AGC off)
1/60(1/50) to
1/100,000 sec.
f3.6mm/F2.0
92.6°
AES ATW 1.0 Vp-p
composite, 75Ω
DC12V±10%
90mA (IR OFF),
280mA (IR ON)±10%
94.1 (phy) x 70.7 (H)
Taiwan

Address - 22, Oasis
Industrial Estate,
opp. Vakola. Masjid
Santacruz (East) Mumbai -
400055
E-mail -
ravinder@gurutek.co.in .
website -
www.gurutek.co.in
Tel - 022 32521053 /
9699031115

