

- Solar Panel: 200mAh 111 volts
- Battery: Li-lon 6 volt 4.5 Ah, C-20
- Back up: 128 hours when fully charged
- LED: 50-130; Color: Red, Yellow, Green or White
- Display thickness: Aluminium Sheet 2mm
- Sheet Metal: 600mm x 600mm x 84mm; Powder coated
- Blinking Frequency: 60 to 72 per minute depending upon conditions
- Reflective Tape: High Intensity Tape of 3M J Avery Dension [Type IXI Type XI]
- Available in different formats / sizes 1 blinking range
- Available for all mandatory, informatory and precautionary signs
- Available in 600mm x 600mm, 900mm x 900mm sizes and Triangular shapes
- Weight: 8 Kgs
- other mandatory / Precautionary / Informatory Signages / Sizes also available

Advantages:

- Green Energy, no Carbon Emission
- No excuse now for implementation of Speed Signs at night
- Oan be installed anywhere, as per requirement
- Automatic operation No operation of ON-OFF required
- No electricity required self sufficient
- No expense of electric wiring
- No digging
- Useful on accident sites to avoid mishaps in the nights
- Useful on Road Construction sites for slowing down motorists
- It gives sense of security on the dark roads giving warning
- Last but least it provides speed direction of movement at busy highways and avoid accidents





ASIAN CONTROLS & EQUIPMENTS

An ISO 9001: 2008

Works: 114, Swapnpoorti, Dr. Ambedkar Road,

Parel, Mumbai 400 012, Ph.: 24156014, Mobile: 9821084620 / 9370069001

E-mail: rhucha@vsnl.com, asian.kulkarni@gmail.com

Office: 36, Trimurti, Parel Village, Parel, Mumbai - 400 012, Ph.: 022 24131460

www:asiancontrols.com