



Mercury & Gas Filled with Contact Gauges

Size Availability:

inches	mm
3.0"	63
4.0"	100
4.5"	115
6.0"	150



Connection: Bottom (Bottom Direct / Surface Mounting)
Back (Centre Back/ Lower Back / Panel / Bracket)

Typical Applications

These gauges are used in Corrosive Medium & Chemical Environments...



Standard Features

- Nominal Sizes:**
63, 100, 115 & 150mm
- Scale Ranges:**
Pressure from -50°C to 650°C
in Fahrenheit / Centigrade / Dual Scale
- Accuracy Class:**
±2.0% of FSD
- Connection:** Bottom (Vertical) /
Back (Horizontal)
1/4", 3/8", 1/2" BSP/NPT, Fix/Adjustable
- Threaded Entry:**
1/4", 1/2" BSP / NPT
- Location of Stem:**
Center Back
- Stem Dia:**
6mm, 8mm, 10mm
- Special Versions / Optional / Extras:**
Surface Mounting,
Panel Mounting,
Bracket Mounting with Distance Capillary
Alarm Contact

- Wetted Part Material:**
SS 304 / SS 316
- Pointer:** Zero Adjustment
- Sensor:**
Mercury / Gas
- Liquid Filling:** Yes
- Over-Range Protection:** 130% of FSD
- Weather Protection:** IP 56
- Window:**
Toughened / Safety Glass
- Case Material:**
Aluminium
- Dial:**
White Aluminium with Red & Black
Lettering

