

Mercury & Gas Filled Temperature Gauges

Size Availability:

The state of the s	
inches	mm
3.0"	63
4.0"	100
4.5"	115
6.0"	150



Connection: Bottom (Bottom Direct / Surface Mounting) Back (Centre Back/ Lower Back / Panel / Bracket)

Typical Applications

: These gauges are used in Corrosive Medium & Chemical Environments...

24

Standard Features

Nominal Sizes:

63, 100, 115 & 150mm

Scale Ranges:

Pressure from -50°C to 650°C in Fahrenheit / Centigrade / Dual Scale

Accuracy Class:

±1.0% of FSD

Connection: Bottom (Vertical) /

Back (Horizontal)

1/4", 3/8", 1/2" BSP/NPT, Fix/Adjustable

Threaded Entry: 1/4", 1/2" BSP / NPT

Location of Stem: Center Back

Stem Dia:

6mm, 8mm, 10mm

Special Versions / Optional / Extras:

Surface Mounting, Panel Mounting, Bracket Mounting with Distance Capillary Alarm Contact



Wetted Part Material:

SS 304 / SS 316

Pointer: Zero Adjustment

Sensor:

Mercury / Gas

Liquid Filling: Yes

Over-Range Protection: 130% of FSD

Weather Protection: IP 56

Window:

Toughened / Safety Glass

Case Material:

SS 304

Dial:

White Aluminium with Red & Black Lettering