

TRIPLE LEVEL WITH GROUND TERMINAL BLOCKS

The CTLG2.5 is a triple level Terminal Block with an additional connection for earthing cables. This separate connection point is appropriately identified by the green - yellow imprint on its top.

This Terminal Block is an ideal choice for motor, sensor, actuator and initiator connections.

Width (Thickness) x Length

Height with DIN 35 x 7.5 / 35 x 15 / 32 x 15 mm Rail

Connection Possibility as per

With 1 Conductor per clamp	Stranded / Flexible
	Solid
With 2 same size Conductors per clamp	with Ferrule / Lug
	Stranded / Flexible
	with TWIN Ferrule / Lug

Wire Stripping Length

Ratings As Per

Voltage

Current

Torque

Approvals

Insulation Material / Comparative Tracking Index

Rated Impulse Voltage / Pollution Degree

Terminal Block

End Plate

Mounting Rail (Refer Pg. 136 for details)

End Clamp (Refer Pg. 137 for details)

Pre Assembled
Shorting Links

2 pole
3 pole
4 pole
10 pole



Insulated
Pre Assembled
Shorting Links

2 pole
3 pole
4 pole
10 pole



Permanent
Shorting Links

2 pole
3 pole
4 pole
10 pole
10 pole (Breakable)
100 pole



Short Sleeve & Screw for
Permanent Shorting Links



Insulated External
Shorting Links

2 pole
3 pole
4 pole
10 pole



Test Socket




Marking Tags (Refer Pg. 139 for details)



Screw Driver



CTLG2.5



6 x 87.5 mm

66.0 mm / 74.0 mm

IEC	UL - CSA
0.25 - 2.5 mm ²	22 - 12 AWG
0.25 - 4.0 mm ²	22 - 10 AWG
0.25 - 2.5 mm ²	22 - 12 AWG
0.25 - 1.5 mm ²	22 - 14 AWG
0.25 - 1.5 mm ²	22 - 14 AWG

9 mm

IEC60947-7-1 IEC 60079-7 UL-1059 CSA22.2-158

440 V 320 V 600 V 300 V

24 A 21 A 24 A 25 A

0.4 Nm 0.4 Nm 4.5 lb-in 4.5 lb-in



Polyamide 66 / 1

6 KV / 3

Type / Cat. No.	Standard Pack
CTLG2.5	100
EPCTLG2.5	50
CA701	50 m
CA701-15	50 m
CA501	50 m
CA702	50
CA802	50
CA202	50
CA627/2	Imax.: 24 A 100
CA627/3	24 A 100
CA627/4	24 A 100
CA627/10	24 A 10
CA647/2	Imax.: 24 A 100
CA647/3	24 A 100
CA647/4	24 A 100
CA647/10	24 A 10
CA703/1	Imax.: 24 A 100
CA704/1	24 A 100
CA705/1	24 A 100
CA732/10	24 A 100
CA732/10-A	24 A 100
CA732/100	24 A 10
CA611/S/Q	100
CA715/2	Imax.: 24 A 100
CA715/3	24 A 100
CA715/4	24 A 100
CA715/10	24 A 20
CA707/TS/01	100
CA509/K2G	100
SCS0.5/3	Blade size: 0.5 x 3 mm 10