

# HOW SECURE ARE YOUR WHEELS?







- Keeps the wheel nuts in place!



# Loose Wheel Nuts: A Serious Issue What is the cost of a wheel falling off?

- Damage to the Rim, Nuts, Bolts and Hub
- Damaged Tyre
- Damage to Other Chassis-parts
- Lost Time and Interruption (Breakdown)
- Overtime

The costs can easily run to thousands! The worst case scenario is that serious injury can result from an accident

### **ROLLOCK** solves the problem



Many truck owners are helpless in finding a solution to make the wheel nuts of their heavy vehicles stay put.

Loose nuts do not only result in wheels falling off, but also significant costs and in some cases can lead to serious accidents.

With Rollock locking clamps the problem is solved.

Vehicles that are used for passenger traffic should always use Rollock locking clamps.



Rollock Wheel Nut Clamps are an inexpensive way to guarantee wheel nut security, virtually eliminating potential wheel loss, costs and injuries from loose wheel nuts.





#### Rollock locking clamps are available in the following sizes:

Rim	No. studs x bolt circle dia.	Nut Size	Rollock Clamp
16"	6 x 205 mm	24-27 mm	104 cc 24-27
17,5"	10 x 225 mm	30-33 mm	70 cc 30-33
19,5"	8 x 275 mm	30-33 mm	104 cc 30-33
22,5"	10 x 335 mm	30-33 mm	104 cc 30-33
17,5"	10 x 8.75"	30-33 mm	70 cc 30-33
22,5"/24,5"	10 x 11.25"	30-33 mm	88 cc 30-33



## **ROLLOCK** is easy to install

Each clamp locks two nuts and is very easy to fit. All you need is our easy to use tool and a plastic-faced hammer. Just drive the locking clamp over two adjacent nuts. The teeth form themselves tightly around the six sides of the nuts and that's it!



The nuts will remain safely in place, securely locked – minimizing the risk of wheel loss.

# **ROLLOCK** is easy to remove

The ingenious Rollock leaves no marks and is easy to remove. Unscrew the wheel nut in the normal manner and the clamp will come off easily.

If you have any questions about ROLLOCK, or would like more information, please do not hesitate to contact us!





Plogvägen 3 • 467 30 GRÄSTORP

Tel: 020-121 025 • Fax: 0514 292 40

www.safetyseal.se