

4½ DIGIT DIGITAL MULTIMETER WITH TERMINAL BLOCKING PROTECTION

10 FUNCTIONS 30 RANGES
Model - KM 6050

FEATURES :

- Low power consumption CMOS double integration, A/D transform integrated circuit
- Auto zero Calibration,
- Auto polarity display,
- Data hold,
- low battery and Over - range indication.
- Test lead jack mechanical protection function and full range over - load protection function.
- Auto power off function

ACCESSORIES :

Test lead pair, Carrying case, Holster & User's Manual

GENERAL SPECIFICATIONS :

- * Sensing : Average Sensing.
- * Basic Accuracy : $\pm 0.05\%$
- * Capacitance measurement : 0-200 μ F
- * Display : 4½ digit 19999 counts Large LCD display
- * Display Size : 70 x 48mm
- * Digit Size : 28mm
- * Low battery indication : " " will occur on the left top of the LCD.
- * Operation Temperature : 0°C ~ 50°C; <85% R.H.
- * Storage Temperature : -10°C ~ 60°C; <85% R.H.
- * Power : Standard 9V battery.
- * Dimension : 192(L) x 88(W) x 42(H)mm
- * Weight : approx.400g (including battery and holster)

OPTIONAL ACCESSORIES :

Current Clamp CA 300, Current Clamp Adaptor CA500, CA1000, CA2000, High Voltage Probe PD-28.

ELECTRICAL SPECIFICATIONS - KM 6050

Accuracy : $\pm$ (%reading + digit)

Environment Temperature : 23°C $\pm$ 5°C. Relative Humidity : <75%

DC VOLTAGE

Range	Resolution	Accuracy
200 mV	10 V	$\pm(0.05\%rdg + 5dgts)$
2 V	100 V	$\pm(0.05\%rdg + 5dgts)$
20 V	1 mV	$\pm(0.05\%rdg + 5dgts)$
200 V	10 mV	$\pm(0.05\%rdg + 5dgts)$
1000 V	100 mV	$\pm(0.1\%rdg + 5dgts)$

Input Impedance : 10M

Overload Protection : 250V (for 200mV) DC or AC peak value.
1000V (for other ranges)

DC CURRENT

Range	Resolution	Accuracy
2 mA	100 nA	$\pm(0.5\%rdg + 2dgts)$
20 mA	1 A	$\pm(0.5\%rdg + 2dgts)$
200 mA	10 A	$\pm(0.75\%rdg + 5dgts)$
20 A	1 mA	$\pm(2\%rdg + 10dgts)$

Overload Protection : 0.2A / 250V fuse

Maximum input current : 20A (15 second max.)

Voltage drop measurement : Full-scale Voltage drop : 200mV

RESISTANCE

Range	Resolution	Accuracy
200	10 m	$\pm(0.2\%rdg + 5dgts)$
2 K	100 m	$\pm(0.2\%rdg + 1dgts)$
20 K	1	$\pm(0.2\%rdg + 1dgts)$
200 K	10	$\pm(0.2\%rdg + 1dgts)$
2 M	100	$\pm(0.2\%rdg + 1dgts)$
20 M	1 K	$\pm(0.5\%rdg + 5dgts)$
200 M	10 K	$\pm(0.5\%rdg + 10dgts)$

Overload Protection : 250V DC or AC peak value

Open circuit Voltage : <1V (2.8V in the 200M range).

Note : It is normal if the test lead short-circuit displays approx. 10 digits in the 200M position.
Please deduct these 10 digits when measuring.

AC VOLTAGE

Range	Resolution	Accuracy
2 V	100 V	$\pm(0.8\%rdg + 10dgts)$
20 V	1 mV	$\pm(0.8\%rdg + 10dgts)$
200 V	10 mV	$\pm(0.8\%rdg + 10dgts)$
1000 V	100 mV	$\pm(1.2\%rdg + 15dgts)$

Input Impedance : 2M

Frequency range : 40Hz - 400Hz

Overload Protection : 250V, (for 200mV) DC or AC peak value.
1000 V (for other ranges)

Display : Average value (Sine RMS)

AC CURRENT

Range	Resolution	Accuracy
2 mA	100 nA	$\pm(0.8\%rdg + 10dgts)$
20 mA	1 A	$\pm(0.8\%rdg + 10dgts)$
200 mA	10 A	$\pm(1.5\%rdg + 10dgts)$
20 A	1 mA	$\pm(2\%rdg + 10dgts)$

Overload Protection : 0.2A / 250V fuse

Maximum input current : 20A (15 second max.)

Voltage drop measurement : Full-scale Voltage drop : 200mV

Frequency Range : 40Hz ~ 400Hz

Display : Average value (Sine RMS)

CAPACITANCE

Range	Resolution	Accuracy
2 nF	0.1 pF	$\pm(2.5\%rdg + 10dgts)$
20 nF	1 pF	$\pm(2.5\%rdg + 10dgts)$
200 nF	10 pF	$\pm(2.5\%rdg + 10dgts)$
2 F	100 pF	$\pm(2.5\%rdg + 10dgts)$
200 F	10 nF	$\pm(5\%rdg + 3dgts)$

Frequency measurement : approx. 400Hz

Voltage drop measurement : approx. 40mV



FREQUENCY

Range	20 kHz
Resolution	1 Hz
Accuracy	$\pm(2\%rdg + 5dgts)$

Overload Protection : 250V DC or AC peak value.

Input sensitivity : 150 mV RMS.

TRIODE hFE PARAMETER MEASUREMENT

Range	Description
hFE	It can measure NPN or PNP type transistor triode hFE parameter. Indication range: 0-1000

Test Condition: 1b approx 10 A
Vce approx 2.8V

DIODE & CONTINUITY MEASUREMENT

Range	Description
→	Indicate forward Voltage drop of diode
Test Condition	
Forward-way current is approx 1mA, contry-way voltage is approx 2.8V	
(((o	The buzzer will beep when resistance approx <30
Test Condition	
Open circuit voltage is approx 2.8V	

Overload Protection : 250V, DC or AC peak value.

All Specifications are subject to change without prior notice