



Moisture Meters Ltd, Westgate Bradford, BD1 3SQ. Tel ++44(0)1274 733582, Fax: ++44(0)1274 370151, e-mail: mail@shawmeters.com, URL: www.shawmeters.com



SADP Digital Specification

Accuracy:	Sensor accuracy typically 1PPM equivalent i.e. +/-3 or 4 deg. C DP
Type:	<p>SADP D Portable hygrometer in stove enamelled zinc plated steel and alloy case, complete with padded carrying case. For table top or portable use with dessicant chamber for rapid readings.</p> <p>ATEX: Intrinsically Safe Class I, Zone 0 AEx ia IIB + H2 T6</p> <p>FM: Intrinsically Safe Class I. Division 1, Groups A & B, C, D T6 (pending)</p>
Dimensions / Weight:	Overall dimensions: 202mm x 225mm x 276mm High (320mm with head extended) Weight: 4 Kg approx.
Display:	Bold Digital Liquid Crystal Display 2cm Digits, Indicating Dewpoint only.
Sensor Connection:	Internal.
Power Supply:	9V DC (6 C type cells) Internal
Sampling:	Pressure: atmospheric with flow rate of 5 - 10 litres/minute
Outputs:	None.
Calibration:	Autocal on all but Blue ranges.
Accessories / Options:	SU4 Lo, Med or Hi Sample system for sample conditioning pressurised gases to atmospheric conditions and controlled flow.
Sensor Type (r): Purple: (P)* Blue: (BL)* Grey : (GY)*	Sensor Range: -100 / 0 deg.C DP, (auto-cal) -80 / +20 deg.C DP (manual-cal) -80 / 0 deg.C DP, (auto-cal)
To Order: *	SADP Dg(r):. Check availability of all these meters.