

PORTABLE DEW- POINT METER- HLS-PDP



PORTABLE/ ON-LINE, DEW POINT-C/ PPM (V), MOISTURE METER MAINS/ BATTERY operated

- One Moisture Sensor- High capacitance Al₂O₃
- Ranges options available—
 - 1) -100°C / +20°C [0.01 to 23000 ppm (V)],
 - 2) -65°C / +20°C [5.5 to 23000 ppm (V)].
- Resolution--- 0.1°C DP with converter reading in PPm (V)
- Accuracy----- +/- 2 deg C Dew point
- Sensor Connections-- Internal
- Calibration --- Manual cal – (At site by user)
- Sensor with desiccant dryer assembly for fast response
No need to use purging gas to keep the sensor dry.
- Power supply Options --● mains 110ac, 230V ac or maintenance-free rechargeable battery,
- Out-Puts options—4-20mA, RS485,
Alarms--- H, HH.
- Cabinet: Table mount / Panel mount
- Operational Area: - Safe Area.

In the interest of continued product up-gradation there may be change in the specifications

Hemaki
LAB-SERVICES

252-D Amar Gian Industrial Estate, L..B.S. Marg, Khopat, Thane (W) 400 6
Maharashtra, India Tel. +91 (022) 2547 49 01 Telefax : 2547 58 68
Email : hemaki@vsnl.com Web site : www.hemaki.com