




SLIP ON FLANGES ANSI ASTM B16.5



300 LBS

Size		raised	base	thick.	dia. of	thru.	bore		dia. of	approx
		face	of hub		bolt	hub			bolt	weight
	D	G	X	t	circle	T2	B2		holes	
size	in	in	in	in	in	in	in	no. of	in	Pounds
DN	mm	mm	mm	mm	mm	mm	mm	holes	mm	KG
1/2"	3.75	1.38	1.5	0.56	2.62	0.88	0.88	4	0.62	1.40
	95.3	34.9	38.1	14.2	66.7	22.4	22.4	4	16	0.64
3/4"	4.62	1.69	1.88	0.62	3.25	1	1.09	4	0.75	2.50
	117.3	42.9	47.6	15.7	82.5	25.4	27.7	4	20	1.12
1"	4.88	2	2.12	0.69	3.5	1.06	1.36	4	0.75	3.00
	123.9	50.8	53.8	17.5	88.9	26.9	34.5	4	20	1.36
1 1/4"	5.25	2.5	2.5	0.75	3.88	1.06	1.7	4	0.75	3.70
	133.4	63.5	63.5	19.1	98.4	26.9	43.2	4	20	1.68
1 1/2"	6.12	2.88	2.75	0.81	4.5	1.19	1.95	4	.88	5.50
	155.4	73	69.9	20.6	114.3	30.2	49.5	4	23	2.49
2"	6.5	3.62	3.31	0.88	5	1.31	2.44	8	0.75	6.30
	165	92.1	84.1	22.4	127	33.3	62	8	20	2.87
2 1/2"	7.5	4.12	3.94	1	5.88	1.5	2.94	8	0.88	9.50
	190.5	104.8	100	25.4	149.2	38.1	74.7	8	23	4.32
3"	8.25	5	4.62	1.12	6.62	1.69	3.57	8	0.88	12.90
	209.6	127	117.5	28.4	168.3	42.9	90.7	8	23	5.85
3 1/2"	9	5.5	5.25	1.19	7.25	1.75	4.07	8	0.88	16.20
	228.6	139.7	133.3	30.2	184.1	44.5	103.4	8	23	7.34
4"	10	6.19	5.75	1.25	7.88	1.88	4.57	8	0.88	21.20
	254	157.2	146	31.8	200	47.8	116.1	8	32	9.61
5"	11	7.31	7	1.38	9.25	2	5.66	8	0.88	27.10
	279	185.7	177.8	35.1	234.9	50.8	143.8	8	23	12.30
6"	12.5	8.5	8.12	1.44	10.62	2.06	6.72	12	0.88	34.40
	317.5	215.9	206.4	36.6	269.9	52.3	170.7	12	23	15.60
8"	15	10.62	10.25	1.62	13	2.44	8.72	12	1	53.30
	381	269.9	260.3	41.1	330.2	62	221.5	12	26	24.20
10"	17.5	12.75	12.62	1.88	15.25	2.62	10.88	16	1.12	75.10
	444.5	323.8	320.7	47.8	387.3	66.5	276.4	16	29	34.10
12"	20.5	15	14.75	2	17.75	2.88	12.88	16	1.25	110.00
	520.7	381	374.6	50.8	450.8	73.2	327.2	16	32	49.80
14"	23	16.25	16.75	2.12	20.25	3	14.14	20	1.25	154.00
	584.2	412.8	425.5	53.8	514.3	76.2	359.2	20	32	69.90
16"	25.5	18.5	19	2.25	22.5	3.25	16.16	20	1.38	194.00
	647.7	469.9	482.6	57.2	571.5	82.6	410.5	20	35	88.10
18"	28	21	21	2.38	24.75	3.5	18.18	24	1.38	240.00
	711.2	533.4	533.4	60.5	628.6	88.9	461.8	24	35	109.00
20"	30.5	23	23.12	2.5	27	3.75	20.1	24	1.38	295.00
	774.7	584.2	587.4	63.5	685.8	95.3	513.1	24	35	134.00
24"	36	27.25	27.62	2.75	32	4.19	24.25	24	1.62	443.00
	914.4	692.2	701.7	69.9	812.8	106.4	616	24	42	201